

Safe and reliable Area secure sensor

- Applicable for the safety detection of automatic assembly line, elevator, danger restricted zone, metal forming machine, punching & shearing machine tool, paper cutter and so on and has protection function.
- Adopting synchronism scanning technology, concentrated beam path, no n working blind area, strong anti-interference ability, and convenient installation.
- Resistance to mutual interference function. It is possible to closely mount more than 2 sets of devices.
- Fault self-check, function, power failure stop, inner component fault stop, connection fault stop, object invading stop signal output.
- Attached with specific control supplying powerful control function.
- Replaceable for similar products made by SICK, STI, KEYENCE, Honeywell Corp.



Detection way	Model	Detection distance	Optic axis distance	Optic axis number	Detection width	Min. detectable object
Through-beam	IDM40-4	≤3m	40mm	4	120mm	Φ 50mm
	IDM40-6			6	200mm	
	IDM40-8			8	280mm	
	IDM40-10			10	360mm	
	IDM40-12			12	440mm	
	IDM40-16			16	600mm	
	IDM40-20			20	760mm	
	IDM40-24			24	920mm	
	IDM40-32			32	1240mm	
	IDM40-40			40	1560mm	
	IDM40-56			56	2200mm	
	IDM40-64			64	2520mm	
Trough-beam	IDM20-4	≤3m	20mm	4	60mm	Φ 30mm
	IDM20-6			6	100mm	
	IDM20-8			8	140mm	
	IDM20-10			10	180mm	
	IDM20-12			12	220mm	
	IDM20-16			16	300mm	
	IDM20-20			20	380mm	
	IDM20-24			24	460mm	
	IDM20-32			32	620mm	
	IDM20-40			40	780mm	
	IDM20-56			56	1100mm	
	IDM20-64			64	1260mm	

WELL CONTACTS CO

56, Pushpak Cascade Swathi Road, Shanthinagar, Bengaluru -560 071.

Tel-080 77726675, 77206675, 41169654 FAX-080 77726675

Email: wclblore_2007@yahoo.com, wclcontacts@yahoo.com