









Outward appearance code		CID12	CID18	CID20	CID30
Appearance					
Dimension					
Detection distance		0-5mm		0-10mm	
DC	NO	CID18-3005NA		CID30-3010NA	
	NC	CID18-3005NB		CID30-3010NB	
6~36 VDC	NO+NC	CID18-3005NC		CID30-3010NC	
	NO	CID18-3005PA		CID30-3010PA	
PNP	NC	CID18-3005PB		CID30-3010PB	
	NO+NC	CID18-3005PC		CID30-3010PC	
AC 90~250 VAC	NO	CID18-3005A		CID30-2010A	
	NC	CID18-3005B		CID30-2010B	
Detection distance		4mm	0-8mm	0-10mm	0-15mm
DC	NO	CID12-3004NA	CID18-3008NA	CID20-3010NA	CID30-3015NA
	NC	CID12-3004NB	CID18-3008NB	CID20-3010NB	CID30-3015NB
6~36 VDC	NO+NC		CID18-3008NC	CID20-3010NC	CID30-3015NC
	NO	CID12-3004PA	CID18-3008PA	CID20-3010PA	CID30-3015PA
PNP	NC	CID12-3004PB	CID18-3008PB	CID20-3010PB	CID30-3015PB
	NO+NC		CID18-3008PC	CID20-3010PC	CID30-3015PC
AC 90~250 VAC	NO		CID18-2008A	CID20-2010A	CID30-2015A
	NC		CID18-2008B	CID20-2010B	CID30-2015B
Detectable object		conductor and dielectric body			
Consumption current		DC<15mA, AC<10mA			
Output current		DC<3V, AC<10V			
Output voltage drop		DC (NPN,PNP) <3V,AC:<7V			
DC/AC Response frequency		DC50Hz,AC:20Hz			
Shell material		Metal	Metal ARS Resin,	ARS Resin	Metal
Working environment temperature		+25℃~+70℃			
Insulation resistance		50MΩ			
Protection standard		IEC standard IP67			
Alternative model at home and abroad		LJC18A3-□□		E2K-X15M-□	

## WELL CONTACTS CO

# 56, "Pushpak Cascade" Swathi Road, Shanthinagar, Bengaluru -560 007.

Tel-080 77726675, 77206675, 41169654 FAX-080 77726675

Email: woblre 2007@yahoo.com, wellcontacts@yahoo.com