













Structural category		IDF2	IDF3	IDF4	IDF5
Outward appearance code					
Outward appearance illustration					
Overall dimensions					
Detection distance		5mm	5mm	5mm	2mm
Flush	NO	IDF2-3005NA	IDF3-3005NA	IDF4-3005NA	IDF5-3002NA
	NC	IDF2-3005NB	IDF3-3005NB	IDF4-3005NB	IDF5-3002NB
	NO+NC			IDF4-3005NC	IDF5-3002NC
	NO	IDF2-3005PA	IDF3-3005PA	IDF4-3005PA	IDF5-3002PA
	NC	IDF2-3005PB	IDF3-3005PB	IDF4-3005PB	IDF5-3002PB
	NO+NC			IDF4-3005PC	IDF5-3002PC
	two wire system	IDF2-3005LA	IDF3-3005LA	IDF4-3005LA	IDF5-3002LA
	NC	IDF2-3005LB	IDF3-3005LB	IDF4-3005LB	IDF5-3002LB
	NO				
	SCR Control-labile silicon				
VAC					
Relay output					
Detection distance					10mm
Non-flush	NO				IDF5-3004NA
	NC				IDF5-3004NB
	NO+NC				IDF5-3004NC
	NO				IDF5-3004PA
	NC				IDF5-3004PB
	NO+NC				IDF5-3004PC
	two wire system				IDF5-3004LA
	NC				IDF5-3004LB
	NO				
	SCR Control-labile silicon				
VAC					
Relay output					
Control output	DC	200mA	200mA	200mA	200mA
	SCR/Relay	300mA	300mA	300mA	300mA
Output voltage dropDC/AC		DC<3V, AC<10V			
Consumption current		DC<15mA, AC<10mA			
Standard detected object		20×20×1(A3 iron)	20×20×1(A3 iron)	20×20×1(A3 iron)	15×15×1(A3 iron)
Repeated precision		0.02	0.02	0.03	0.03
DC/AC Response frequency		400Hz/25Hz	400Hz/25Hz	300Hz	400Hz
Working environment temperature		+25℃~+75℃	+25℃~+75℃	+25℃~+75℃	+25℃~+75℃
Insulation resistance		≥50MΩ	≥50MΩ	50MΩ	≥50MΩ
Shell material		ABS Resin	ABS Resin	ABS Resin	ABS Resin
Protection grade		IP67	IP67	IP67	IP67
Alternative model at home and abroad		TL-QTMC1	PS17-5PN	PS05-N, PS05-P	

### WELL CONTACTS CO

# 56, "Pushpak Cascade" Swathi Road, Shanthinagar, Bengaluru -560 027.

Tel-080 22226675, 22206675, 41169654 FAX-080 22226675

Email: wcblore\_2007@yahoo.com, wellcontacts@yahoo.com